



SAFETY DATA SHEET

1. Identification

Product identifier	BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Deep Base	
Other means of identification		
Product code	5340	
Recommended use	Architectural Coating	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Supplier	Behr Process LLC 1801 E. St. Andrew Place Santa Ana, CA 92705	
Telephone	714-545-7101	
Emergency telephone	+1 760 476 3962 +1 866 519 4752	
Access code	335213	

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Hazards for the product as sold

Health hazards	Sensitization, skin	Category 1
	Carcinogenicity	Category 1B

Hazards for the product as sold

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Kaolin	1332-58-7	1 - 5



Chemical name	CAS number	%
2-Butoxyethyl benzoate	5451-76-3	0.5 - 1.5
Diphenyl ketone	119-61-9	0.1 - 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	0 - 0.1
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	0 - 0.1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Opaque.
Odor	Slight.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 99 °F (> 37.22 °C)
Flammability	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Flash point	Not applicable. Property has not been measured.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Property has not been measured.
pH	7 - 10
pH concentration	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Kinematic viscosity temp	Property has not been measured.
Solubility	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Property has not been measured.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Density and/or relative density	
Density	8.87 lb/gal
Relative density	Property has not been measured.
Relative density temperature	Property has not been measured.
Vapor density	Property has not been measured.
Vapor density temp.	Property has not been measured.
Particle characteristics	Not available.
Other information	
Dynamic viscosity	Property has not been measured.
Dynamic viscosity temp	Property has not been measured.
Viscosity	50 - 140 ku
VOC	46 g/l (excluding water) (Coating) 14 g/l (including water) (Material)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Product	Species	Test Results
---------	---------	--------------

BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Deep Base (CAS Mixture)

Acute

Dermal

ATEmix		1024000 mg/kg bw
--------	--	------------------

Components	Species	Test Results
------------	---------	--------------

Diphenyl ketone (CAS 119-61-9)

Acute

Dermal

LD50	Rabbit	3535 mg/kg
------	--------	------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diphenyl ketone (CAS 119-61-9)	2B Possibly carcinogenic to humans.
--------------------------------	-------------------------------------

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to IMO instruments	Not available.

15. Regulatory information

US federal regulations	
Toxic Substances Control Act (TSCA)	All components are listed on or exempt from the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	
2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4)	1.0 % Subject to One-Time Reporting Requirements (Per Country)
5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4)	1.0 % One-Time Export Notification only.
CERCLA Hazardous Substance List (40 CFR 302.4)	
2-Butoxyethyl benzoate (CAS 5451-76-3)	
Ammonium hydroxide (CAS 1336-21-6)	
SARA 304 Emergency release notification	
Ammonium hydroxide (CAS 1336-21-6)	100 LBS
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Ammonium hydroxide	1336-21-6	100	500		

SARA 311/312 Hazardous chemical

Classified hazard categories	Respiratory or skin sensitization Carcinogenicity
-------------------------------------	--

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ammonium hydroxide	1336-21-6	0.2 - < 31

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Butoxyethyl benzoate (CAS 5451-76-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)

Kaolin (CAS 1332-58-7)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethyl benzoate (CAS 5451-76-3)

Ammonium hydroxide (CAS 1336-21-6)

Kaolin (CAS 1332-58-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethyl benzoate (CAS 5451-76-3)

Ammonium hydroxide (CAS 1336-21-6)

Kaolin (CAS 1332-58-7)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)

Kaolin (CAS 1332-58-7)

16. Other information, including date of preparation or last revision

Issue date 05-December-2019

Revision date 15-January-2026

Version # 02

HMIS® ratings Health: 2*
Flammability: 0
Physical hazard: 0

References IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Behr Process LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.