



SAFETY DATA SHEET

1. Identification

Product identifier New Generation™ Wheel Bearing Grease for Disc and Drum Brakes

Other means of identification

Product code SL3110, SL3111, SL3116

Recommended use Wheel bearing grease for disc and drum brakes

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2A

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye/face protection. Avoid release to the environment.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information

95% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 95% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	50 - 60
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	40 - 50
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		68649-42-3	3 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Call a physician if symptoms develop or persist.
Skin contact	Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritating to mouth, throat, and stomach.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Avoid dust formation. Clean surface thoroughly to remove residual contamination. Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, please see the product label.
Conditions for safe storage, including any incompatibilities	Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Latex. Rubber.

Other Wear suitable protective clothing.

Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Grease.
Color	Amber.
Odor	Mild petroleum.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	680 °F (360 °C) estimated
Flash point	> 450 °F (> 232.2 °C)
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	< 0.1 mm Hg @ 68 °F
Vapor density	> 5 (air = 1)
Relative density	0.9
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Causes serious eye irritation.

Ingestion	Irritating to mouth, throat, and stomach.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not available.

Product	Species	Test Results
New Generation™ Wheel Bearing Grease for Disc and Drum Brakes		
Acute		
Dermal		
LD50	Rabbit	3226 mg/kg estimated
Oral		
LD50	Rat	5263 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
New Generation™ Wheel Bearing Grease for Disc and Drum Brakes		
Aquatic		
Crustacea	EC50 Daphnia	32.8948 mg/l, 48 hours estimated
Fish	LC50 Fish	180.6833 mg/l, 96 hours estimated
Components	Species	Test Results

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1000 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1 - 5 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Fathead minnow (Pimephales promelas) 1 - 5 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.
SARA 304 Emergency release notification	Not regulated.
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)
CERCLA Hazardous Substance List (40 CFR 302.4)	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3) Listed.
CERCLA Hazardous Substances: Reportable quantity	Not listed.
	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not regulated.
Safe Drinking Water Act (SDWA)	Not regulated.
Food and Drug Administration (FDA)	Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312	Immediate Hazard - Yes
Hazard categories	Delayed Hazard - No
	Fire Hazard - No
	Pressure Hazard - No
	Reactivity Hazard - No
SARA 302 Extremely hazardous substance	No

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
 Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)
 Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
 Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. Massachusetts RTK - Substance List

None.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations**EPA**

VOC content (40 CFR 51.100(s)) 2.2 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products Not regulated

VOC content (CA) 2.2 %

VOC content (OTC) 2.2 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-11-2015
Revision date 07-24-2015
Prepared by Allison Cho
Version # 02
Further information Not available.
HMIS® ratings Health: 1
Flammability: 1
Physical hazard: 0
Personal protection: B
NFPA ratings Health: 1
Flammability: 1
Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.