



SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: Flex Seal Flood Protection

Other means of identification

SDS number: RFSYELR16; RFSYELR24 AND US573YEL 16

Recommended restrictions

Recommended use: Coating

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Company Name: SWIFT RESPONSE, LLC
Address: 2690 WESTON RD.
WESTON, FL 33331
US

Telephone: 833-411-3539

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Toxic to reproduction Category 2
Specific Target Organ Toxicity -
Single Exposure Category 3
(Narcotic effect.)
Specific Target Organ Toxicity -
Repeated Exposure Category 2
Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic
environment Category 2

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Extremely flammable aerosol. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Toxic to aquatic life. Contains gas under pressure; may explode if heated.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	25 - <50%
Propane	74-98-6	10 - <20%
Propane, 2-methyl-	75-28-5	10 - <20%
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	10 - <25%
Naphtha (petroleum), heavy alkylate	64741-65-7	1 - <5%
Limestone	1317-65-3	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Personal Protection for First-aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.
-------------------	--

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.
--	---

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Accidental release measures:	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

No data available.

Safe handling advice:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin. Wash hands thoroughly after handling.

Contact avoidance measures:

No data available.

Storage

Safe storage conditions:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

Safe packaging materials:

No data available.

Storage Temperature:

No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values		Source
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
Propane	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Propane, 2-methyl-	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), light distillate hydrotreating process, low-boiling - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

Naphtha (petroleum), heavy alkylate	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Limestone - Total	REL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Limestone - Respirable.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Limestone - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Limestone - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Limestone - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Limestone - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Zeolites - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values, as amended
White mineral oil (petroleum) - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
White mineral oil (petroleum) - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Benzene, dimethyl-	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Stoddard solvent	TWA	100 ppm	525 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable dust.	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Crystalline Silica - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended
Crystalline Silica - Respirable dust.	TWA		0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable dust.	TWA		0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
Crystalline Silica - Respirable dust.	PEL		0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable dust.	OSHA_ACT		0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
Acetic acid, butyl ester	REL	150 ppm	710 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	200 ppm	950 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	150 ppm	710 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	200 ppm	950 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended

	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, 1,2,4-trimethyl-	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values, as amended
Naphthalene	STEL	15 ppm	75 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	10 ppm	50 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	10 ppm	50 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	10 ppm	50 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	15 ppm	75 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	OSHA ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL
Benzene, dimethyl- (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL

Exposure guidelines

Naphthalene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
Benzene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

No data available.

Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	When using do not smoke. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Freezing point:	No data available.
Boiling Point:	No data available.
Flash Point:	Estimated -104 °C
Evaporation Rate:	No data available.
Flammability (solid, gas):	No data available.
Explosive limit - upper (%):	Estimated 9.5 %(V)
Explosive limit - lower (%):	Estimated 1.8 %(V)
Vapor pressure:	3,792 - 5,171 hPa (20 °C) 7,584 - 8,963 hPa (54 °C)
Vapor density (air=1):	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility in Water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Self Ignition Temperature:	No data available.
Decomposition Temperature:	No data available.
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.

Hazardous Decomposition Products: No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.
Skin Contact: No data available.
Eye contact: No data available.
Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.
Skin Contact: No data available.
Eye contact: No data available.
Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product: ATEmix: 47,619.05 mg/kg
Dermal Product: ATEmix: 17,958.16 mg/kg
Inhalation Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

Benzene, methyl- LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target Organ(s): Liver, Kidney) Oral Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation Experimental result, Key study
Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Propane, 2-methyl- NOAEL (Rat(Female, Male), Inhalation, >= 42 d): 16,000 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation): 21,394 mg/m3 Inhalation Experimental result, Key study
Distillates (petroleum), light distillate NOAEL (Rat(Female, Male), Inhalation): 9,840 mg/m3 Inhalation Experimental result, Key study
hydrotreating process, low-boiling NOAEL (Rat(Male), Oral, 28 d): < 500 mg/kg Oral Experimental result, Supporting study
NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

Benzene, methyl-Distillates (petroleum), light distillate	in vivo (Rabbit): Irritating
hydrotreating process, low-boiling	Assessment Not irritating

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

Benzene, methyl-Distillates (petroleum), light distillate	Rabbit, 24 - 72 hrs: Not irritating
hydrotreating process, low-boiling	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

Benzene, methyl-Distillates (petroleum), light distillate	Skin sensitization:, in vivo (Guinea pig): Non sensitising
hydrotreating process, low-boiling	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro**

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Components:

Benzene, methyl-	Suspected of damaging fertility or the unborn child.
------------------	--

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Components:

Benzene, methyl-	Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
------------------	--

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Components:

Benzene, methyl- Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Components:

Benzene, methyl- May be fatal if swallowed and enters airways.

Distillates (petroleum), light distillate May be fatal if swallowed and enters airways.

hydrotreating process, low-boiling

Naphtha (petroleum), heavy alkylate May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Distillates (petroleum), light distillate LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study
hydrotreating process, low-boiling

Aquatic Invertebrates

Product: No data available.

Components:

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality
LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

Distillates (petroleum), light distillate EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
hydrotreating process, low-boiling NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study
LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Distillates (petroleum),
light distillate
hydrotreating process,
low-boiling

NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting study

Aquatic Invertebrates

Product:

No data available.

Components:

Benzene, methyl-

LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study
NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

Distillates (petroleum),
light distillate
hydrotreating process,
low-boiling

NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.

Components:

Benzene, methyl-

100 % (14 d) Detected in water. Experimental result, Weight of Evidence study
86 % Detected in water. Experimental result, Weight of Evidence study

Propane

100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Propane, 2-methyl-

100 % Detected in water. QSAR, Weight of Evidence study

Distillates (petroleum),
light distillate
hydrotreating process,
low-boiling

90.35 % (28 d) Detected in water. Experimental result, Supporting study

BOD/COD Ratio

Product:

No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:

No data available.

Components:

Benzene, methyl-

Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment
Experimental result, Key study

Distillates (petroleum),
light distillate
hydrotreating process,
low-boiling

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product:

No data available.

Mobility in soil: No data available.

Components:

Benzene, methyl-	No data available.
Propane	No data available.
Propane, 2-methyl-	No data available.
Distillates (petroleum), light distillate hydrotreating process, low-boiling	No data available.
Naphtha (petroleum), heavy alkylate	No data available.
Limestone	No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
EmS No.:	
Packing Group:	—
Special precautions for user:	None known.

IATA

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Special precautions for user:	None known.
Other information	
Passenger and cargo aircraft:	Allowed. 203
Cargo aircraft only:	Allowed. 203

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
EmS No.:	F-D, S-U
Packing Group:	—
Special precautions for user:	None known.

The classification shown in this section may be eligible for use of an exception, such as "Limited Quantity", per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Crystalline Silica	lung effects immune system effects Cancer
Benzene	kidney effects Flammability Cancer Aspiration Eye Blood Skin respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>
BENZENE, METHYL-
UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY
RCRA HAZARDOUS WASTE NO. D001
XYLENE (MIXED)
BUTYL ACETATE
ETHYLBENZENE
BENZENE,1-METHYLETHYL-
CUMENE
NAPHTHALENE
BENZENE

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Reproductive toxicity,
Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u>	<u>% by weight</u>
Benzene, methyl-	1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including, Benzene which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

This product can expose you to chemicals including, Crystalline Silica, Benzene, ethyl-, Benzene, (1-methylethyl)-, and Naphthalene, which is [are] known to the State of California to cause cancer.

This product can expose you to chemicals including, Benzene, methyl- which is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Benzene, methyl-

Propane

Propane, 2-methyl-

Distillates (petroleum), light distillate hydrotreating process, low-boiling

Naphtha (petroleum), heavy alkylate

Limestone

White mineral oil (petroleum)

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Benzene, methyl-

Propane

Propane, 2-methyl-

Distillates (petroleum), light distillate hydrotreating process, low-boiling

Naphtha (petroleum), heavy alkylate

Limestone

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

Australia AICS	Not in compliance with the inventory.
Canada DSL Inventory List	On or in compliance with the inventory.
Canada NDSL Inventory	Not in compliance with the inventory.
Ontario Inventory	Not in compliance with the inventory.
China Inv. Existing Chemical Substances	On or in compliance with the inventory
Japan (ENCS) List	Not in compliance with the inventory.
Japan ISHL Listing	Not in compliance with the inventory.
Japan Pharmacopoeia Listing	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI)	On or in compliance with the inventory
Mexico INSQ	Not in compliance with the inventory.
New Zealand Inventory of Chemicals	On or in compliance with the inventory
Philippines PICCS	On or in compliance with the inventory
Taiwan Chemical Substance Inventory	On or in compliance with the inventory
US TSCA Inventory	On or in compliance with the inventory
EINECS, ELINCS or NLP	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date: 04/19/2022

Revision Information: No data available.

Version #: 2.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.