



Safety Data Sheet

Issue Date 21-May-2013

Revision Date: 04-Jul-2013

Version 1

1. IDENTIFICATION

Product Identifier

Product Name PC - Woody, Part A

Other means of identification

SDS # 130625-17

Recommended use of the chemical and restrictions on use

Recommended Use Adhesives.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency Telephone Number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Appearance White paste

Physical State Paste

Odor Mild

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Get medical attention if irritation occurs
IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash it before reuse
If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Bisphenol A - Epichlorohydrin polymer	25068-38-6	60-65
Kaolin	1332-58-7	8-10
Hydrous magnesium silicate	14807-96-6	5-7
Wood flour	Proprietary	5-7
Bis(2-ethylhexyl) terephthalate	6422-86-2	4-6
Glycidyl Ethers of Bisphenol F Resin	Proprietary	1-3
Titanium Dioxide	1317-80-2	<1
Polyethylene fiber	Proprietary	<1

Product contains a proprietary mixture of ingredients.

4. FIRST-AID MEASURES**First Aid Measures**

General Advice	Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant, paramedic, or community medical support.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Do not induce vomiting. Clean mouth with water and drink afterwards plenty of water. Seek medical advice.

Most important symptoms and effects

Symptoms	Causes eye irritation. Direct contact may cause temporary redness and discomfort. Causes skin irritation. Can cause respiratory tract irritation. May cause nose, throat, and lung irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Skin and eye conditions may be aggravated by long term exposure. Application of corticosteroid cream has been effective in treating skin irritation.
---------------------------	---

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2). Aldehydes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Wear protective gloves/protective clothing and eye/face protection. Avoid breathing vapors, mist or gas. Remove any contaminated clothing and wash thoroughly before reuse.
For Emergency Responders	Follow applicable OSHA regulations (29 CFR 1910.120).
Environmental Precautions	See Section 12 for additional Ecological Information. Prevent runoff from entering drains, sewers or streams.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an absorbent material.
Methods for Clean-Up	Dispose of contents/container to an approved waste disposal plant. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash face, hands, and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.
Incompatible Materials	Strong oxidizing agents, acids, Amines, Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Hydrous magnesium silicate 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Wood flour	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls	Provide general or local exhaust ventilation if product is sanded or ground.
-----------------------------	--

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Chemical safety goggles/faceshield.
Skin and Body Protection	Wear protective gloves and protective clothing.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Paste	Odor	Mild
Appearance	White paste	Odor Threshold	Not determined
Color	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	No data	

Flash Point	248.88 °C / 480 °F	CC (closed cup)
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	
Lower Flammability Limit	Not available	
Vapor Pressure	Not determined	
Vapor Density	Not available	
Specific Gravity	0.79	(1=Water) @ 4°C
Water Solubility	Insoluble in water	
Solubility in other solvents	Alcohols	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
Density	6.6 lbs/gal	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

Strong oxidizing agents, acids, Amines, Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Causes serious eye irritation.

Skin Contact

Causes skin irritation.

Inhalation

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Ingestion

May cause discomfort if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A - Epichlorohydrin polymer 25068-38-6	= 11400 mg/kg (Rat)	20000 mg/kg (rabbit)	-
Wood flour	> 5 g/kg (Rat)	> 2 g/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h

Information on physical, chemical and toxicological effects**Symptoms**

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

May cause an allergic skin reaction.

Carcinogenicity

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Chemical Name	ACGIH	IARC	NTP	OSHA
Hydrous magnesium silicate 14807-96-6		Group 3		
Polyethylene fiber		Group 3		

*IARC (International Agency for Research on Cancer)
Group 3 IARC components are "not classifiable as human carcinogens"*

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrous magnesium silicate 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations**SARA 313**

Not determined

US State Regulations**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Kaolin 1332-58-7	X	X	X
Hydrous magnesium silicate 14807-96-6	X	X	X
Wood flour	X	X	X
Titanium Dioxide 1317-80-2			X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	B- Safety Glasses, Gloves

Issue Date 21-May-2013
Revision Date: 04-Jul-2013
Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue Date 21-May-2013

Revision Date: 04-Jul-2013

Version 1

1. IDENTIFICATION

Product Identifier

Product Name PC - Woody, Part B

Other means of identification

SDS # 130625-16

Recommended use of the chemical and restrictions on use

Recommended Use Adhesives.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency Telephone Number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Appearance Light brown paste

Physical State Paste

Odor slight amine

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Get medical attention if irritation occurs
IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash it before reuse
If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Styrenated phenol	61788-44-1	30-35
Kaolin	1332-58-7	15-20
Aliphatic Polyaminoamide	68410-23-1	10-12
Polyoxypropylenediamine	9046-10-0	8-10
Talc	14807-96-6	6-8
Wood flour	Proprietary	6-8
N-Aminoethyl piperazine	140-31-8	5-7
Bis(2-ethylhexyl) terephthalate	6422-86-2	5-7

Product contains a proprietary mixture of ingredients.

4. FIRST-AID MEASURES**First Aid Measures**

General Advice	Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant, paramedic, or community medical support.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical advice.

Self-Protection of the First Aider First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Most important symptoms and effects

Symptoms	Causes eye irritation. Direct contact may cause temporary redness and discomfort. Causes skin irritation. Inhalation only possible at elevated temperatures. May cause irritation. May cause an allergic skin reaction.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Skin and eye conditions may be aggravated by long term exposure. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.
---------------------------	---

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂), Dry chemical, Alcohol foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous Combustion Products Carbon monoxide, Carbon dioxide (CO₂), Aldehydes.

Protective equipment and precautions for firefighters

A face shield should be worn. Firefighters should wear butyl rubber boots, gloves, and body suit and a self-contained breathing apparatus. Water spray may be used to cool closed containers exposed to fire. Retain expended liquids from fire fighting for later disposal. Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Wear protective gloves/protective clothing and eye/face protection. Avoid breathing vapors, mist or gas. Remove any contaminated clothing and wash thoroughly before reuse.
For Emergency Responders	Follow applicable OSHA regulations (29 CFR 1910.120).
Environmental Precautions	See Section 12 for additional Ecological Information. Do not release into sewers or waterways.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an absorbent material.
Methods for Clean-Up	Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash face, hands, and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.

Incompatible Materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Wood flour	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Appropriate engineering controls**Engineering Controls**

Provide general or local exhaust ventilation if product is sanded or ground. Suitable emergency eye wash facility should be available in work area.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Chemical safety goggles/faceshield.

Skin and Body Protection

Wear protective gloves and protective clothing.

Respiratory Protection

Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State
Appearance
Color

Paste
Light brown paste
light brown

Odor
Odor Threshold

slight amine
Not determined

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	No data	
Flash Point	248.88 °C / 480 °F	CC (closed cup)
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	
Lower Flammability Limit	Not available	
Vapor Pressure	Not determined	
Vapor Density	Not available	
Specific Gravity	.77	(1=Water) @ 4°C
Water Solubility	Insoluble in water	
Solubility in other solvents	Alcohols	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
Density	6.4 lbs/gal	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Causes serious eye irritation.

Skin Contact

Causes skin irritation.

Inhalation

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Ingestion

May cause discomfort if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrenated phenol 61788-44-1	= 2500 mg/kg (Rat)	> 7940 mg/kg (Rabbit)	-
Aliphatic Polyaminoamide 68410-23-1	>2000 mg/kg (rat)	2000 mg/kg (rat)	-
Polyoxypropylenediamine 9046-10-0	= 1100 mg/kg (Rat)	= 1555 mg/kg (Rabbit)	-
Wood flour	> 5 g/kg (Rat)	> 2 g/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h
N-Aminoethyl piperazine 140-31-8	= 2140 mg/kg (Rat)	= 880 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects**Symptoms**

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

May cause an allergic skin reaction.

Carcinogenicity

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		

IARC (International Agency for Research on Cancer)
Group 3 IARC components are "not classifiable as human carcinogens"

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		
N-Aminoethyl piperazine 140-31-8	495: 72 h Pseudokirchneriella subcapitata mg/L EC50	1950 - 2460: 96 h Pimephales promelas mg/L LC50 flow-through 1000: 96 h Poecilia reticulata mg/L LC50 semi-static 100: 96 h Oncorhynchus mykiss mg/L LC50 semi-static		32: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Styrenated phenol 61788-44-1	>4
N-Aminoethyl piperazine 140-31-8	-1.48

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Contact your supplier or a licensed contractor for detailed recommendations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION**International Inventories**

Not determined

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances***US Federal Regulations****SARA 313**

Not determined

US State RegulationsU.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Kaolin 1332-58-7	X	X	X
Talc 14807-96-6	X	X	X
Wood flour	X	X	X
N-Aminoethyl piperazine 140-31-8	X	X	X

16. OTHER INFORMATIONNFPA**Health Hazards****Flammability****Instability****Special Hazards**

1

1

0

Not determined

HMIS**Health Hazards****Flammability****Physical Hazards****Personal Protection**

1

1

0

B- Safety Glasses,
Gloves**Issue Date**

21-May-2013

Revision Date:

04-Jul-2013

Revision Note

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet